

specifications

Door & side panel construction	GRP compression moulded skins, composite rails and stiles. 100% CFC free polyurethane thermally insulated core
Locking mechanism	Fullex Crimebeater, secured by design. 20mm radiused stainless steel face plate. Tested to PAS23 & PAS24. Fully adjustable keepsets, integral latch snib. Deep throw bolts.
PVC outerframe	Dedicated 70mm chamfered composite door outerframe specifically designed to work with 44mm door leaves incorporating weatherseal channels.
Top box construction	Single piece welded frame using dedicated composite door 'T' transom
Glazing cassette	Screwless clip on glazing cassette
Reinforcing specification	Galvanised steel reinforcement
Door slab edging	2mm PVC edging with Ash grain effect embossing. Trimmed and radiused edges to match door leaf. CNC routed to match radius of lock faceplate and hinges
Hardware colour	Fully suited in gold, chrome and black
Handle type	Lever/Lever. Colour suited to hardware selection
Hinge type	3 no. 100mm butt hinges, colour to suit hardware selection
Hardware performance	BSI Kitemark
Weather rating	PAS23. BSI kitemark if flag hinges upgrade is chosen
Security rating	PAS24. BSI kitemark if flag hinges upgrade is chosen
Number of keys	3
Glass	24mm double glazed toughened sealed units. 28mm sealed units used in top boxes and fully glazed panels
Standard cylinder	35/35 5 pin Euro cylinder with anti-bump cylinder protector. Available in brass and nickel finishes

OPTIONS

Security cylinder	35/35 Mul-T-Lock Break secure Euro cylinder with 7 pin key with anti-jiggle, anti-drill, anti-pick and anti-extraction with two high security keys
Letterplate construction	All metal faceplates and surrounds, suited to match other furniture
Low threshold	Aluminium part 'M' compliant with thermal break and available in silver, gold and black
Extension profile	Colour matched 15mm multi clip on
Flag hinge	3 dimension adjustable. Colour suited with hardware.
Lever pad handle	Colour suited to hardware selection